ACCORDIA
CABLES BEYOND STANDARD

T E C H N I C A L D A T A S H E E T

Accordia LiYCY

Control Cables

Image representative of cable family. Actual cable may vary.

CPR certified

Based on VDE0812

STANDARDS AND CERTIFICATES

Standards	**Based on VDE0812** **EN 60228** **EN 50575**
CPR Class	**Eca**
DOP	**1002683**
ROHS II	**complies**

CONSTRUCTION

Conductors	**Flexible copper class 5**
Insulation	**PVC**
Laying up	**Cores stranded**
Core Identification	**Different colors without repetition, based on DIN 47100**
Screen	**Tinned copper braid**
Outer Sheath	**PVC grey**

ELECTRICAL CHARACTERISTICS

Operation Voltage	**300/500 V**
Insulation Resistance	**>100 MOhm.km**
Test Voltage	**1200 V**
DC Resistance	**0,25mm2 <79,00 Ohm/km** **0,50mm2 <39,00 Ohm/km** **0,75mm2 <26,00 Ohm/km** **1,00mm2 <19,50 Ohm/km** **1,50mm2 <13,30 Ohm/km** **2,50mm2 <7,98 Ohm/km** **4,00mm2 <4,95 Ohm/km**

MECHANICAL CHARACTERISTICS

Minimum bending radius	**10 x Φ outer sheath**
Operation Temperature	**-20 C up to 70 C**
Standard packaging	**5x100m, 1x500m**

APPLICATIONS

SMART BUILDING

SAFETY & SECURITY

INDUSTRIAL

Accordia LiYCY

OUTER DIMENSIONS

No Cores X Cross-section (mm2)	Outer Sheath (mm)
2x0,25	**4,30**
3x0,25	**4,50**
4x0,25	**4,80**
5x0,25	**5,20**
6x0,25	**5,60**
7x0,25	**5,60**
2x0,50	**5,30**
3x0,50	**5,60**
4x0,50	**6,00**
5x0,50	**6,50**
6x0,50	**7,10**
7x0,50	**7,10**
2x0,75	**5,80**
3x0,75	**6,10**
4x0,75	**6,60**
5x0,75	**7,20**
6x0,75	**7,80**
7x0,75	**7,80**
2x1,00	**6,00**
3x1,00	**6,30**
4x1,00	**6,90**
5x1,00	**7,50**
6x1,00	**8,10**
7x1,00	**8,10**
2x1,50	**6,40**
3x1,50	**6,80**
4x1,50	**7,40**
5x1,50	**8,00**
6x1,50	**8,70**
7x1,50	**8,70**
2x2,50	**7,40**
3x2,50	**7,80**
4x2,50	**8,60**
5x2,50	**9,40**
6x2,50	**10,20**
7x2,50	**10,20**
2x4,00	**8,60**
3x4,00	**9,10**
4x4,00	**10,00**
5x4,00	**11,00**
6x4,00	**12,00**
7x4,00	**12,00**

ACCORDIA
CABLES BEYOND STANDARD

Pentalofos, T. 2310 787202
P.O.Box 10229
54012 Thessaloniki - Greece
welcome@accordia.gr
www.accordia.gr