ACCORDIA
CABLES BEYOND STANDARD

T E C H N I C A L D A T A S H E E T

Accordia HSLH B2ca LSZH -OB/-JB/-OZ/-JZ

Control Cables Halogen Free

Image representative of cable family. Actual cable may vary.

CPR Class B2ca s1,d1,a1

FlameSmart technology

Based on DIN EN50363-7/VDE 0207-363-7 & DIN EN50363-8/VDE 0207-363-8

Halogen Free

STANDARDS AND CERTIFICATES

Standards	**Based on DIN EN50363-7/VDE 0207-363-7 & DIN EN50363-8/VDE 0207-363-8 EN 60228 EN 50575**
CPR Class	**B2ca s1,d1,a1**
DOP	**1002705**
ROHS II	**complies**

CONSTRUCTION

Conductors	**Flexible copper class 5**
Insulation	**Low Smoke Zero Halogen (Flame Retardant)**
Laying up	**Cores stranded**
Core Identification	**Different colors without repetition, based on VDE 0293-308, with (-JB) or w/o (-OB) green-yellow core. Black with white number cores available upon request**
Outer Sheath	**Low Smoke Zero Halogen (Flame Retardant) grey**

ELECTRICAL CHARACTERISTICS

Operation Voltage	**300/500 V**
Test Voltage	**2000 V**
DC Resistance	**0,50mm2 <39,00 Ohm/km 0,75mm2 <26,00 Ohm/km 1,00mm2 <19,50 Ohm/km 1,50mm2 <13,30 Ohm/km 2,50mm2 <7,98 Ohm/km 4,00mm2 <4,95 Ohm/km**

MECHANICAL CHARACTERISTICS

Minimum bending radius Fix Installation	**5 x Φ outer sheath**
Operation Temperature Fix Installation	**-20 C up to + 70 C**
Standard packaging	**5x100m, 1x500m**

APPLICATIONS

SMART BUILDING

SAFETY & SECURITY

INDUSTRIAL

Accordia HSLH B2ca LSZH -OB/-JB/-OZ/-JZ

OUTER DIMENSIONS

No Cores X Cross-section (mm2)	Approx. Outer Sheath (mm)
2x0,50	**5,10**
3x0,50	**5,40**
4x0,50	**5,80**
5x0,50	**6,10**
6x0,50	**6,70**
2x0,75	**5,60**
3x0,75	**5,90**
4x0,75	**6,40**
5x0,75	**6,80**
6x0,75	**7,40**
2x1,00	**5,80**
3x1,00	**6,10**
4x1,00	**6,70**
5x1,00	**7,10**
6x1,00	**7,70**
8x1,00	**8,50**
10x1,00	**9,80**
2x1,50	**6,20**
3x1,50	**6,60**
4x1,50	**7,20**
5x1,50	**7,60**
6x1,50	**8,30**
7x1,50	**8,30**
2x2,50	**7,20**
3x2,50	**7,60**
4x2,50	**8,40**
5x2,50	**9,00**
6x2,50	**9,80**
7x2,50	**9,80**
2x4,00	**8,00**
3x4,00	**8,90**
4x4,00	**9,80**
5x4,00	**10,60**
6x4,00	**11,60**
7x4,00	**11,60**

ACCORDIA
CABLES BEYOND STANDARD

Pentalofos, T. 2310 787202
P.O.Box 10229
54012 Thessaloniki - Greece
welcome@accordia.gr
www.accordia.gr